Pressure-sensitive adhesives

Acrylic

#### Paper

# HIBRIGHT SEMIGLOSS ECO / TP200 46#CCK

ITEM #93618

## FACESTOCK

A semi-gloss facestock designed for applications requiring premium label appearance and excellent flexographic (UV, water, and solvent) and rotory offset (UV and conventional) printing.

<b>Type</b> Paper			
Tensile MD	Tensile CD		
22.8	11.4		
Tear MD	Tear CD		
30.6	31.6		
PROPERTIES	VALUE		
Basis Weight	57.4#		
Caliper	2.6 mil		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
<b>FSC</b> No			
*Please contact your sales repr	esentative for details		

#### **ADHESIVE**

An all-purpose water-based acrylic adhesive. Not suitable for HDPE, LDPE, Polyethylene, Polyolefin, or corrugated...

<b>Type</b> Permanent	<b>Composition</b> Acrylic	
PROPERTIES	VALUE	
Glass	3.5 lbs/linear in.	
Polyethylene	1.8	
REGULATORY APPROVAL		
<b>RoHS</b> Yes	<b>Prop65</b> Yes	<b>REACH</b> Yes
трсн	CPSIA	UL

• •		
V /	2	ĉ
- 1 5	-	э

**Direct Food** No Yes

**Indirect Food** Yes

\*Please contact your sales representative for details

### LINER

A clay coated kraft (CCK) liner which has been silicone coated one side and has great directional stability.

<b>Type</b> colacril liner					
Tensile MD	Tensile CD				
5	2				
Tear MD	Tear CD				
38	38	38			
DESCRIPTION	VALUE				
Basis Weight	46				
Caliper	3.2				
REGULATORY APPROVAL					
RoHS	Prop65	REACH			
Yes	Yes	Yes			
ТРСН	CPSIA	UL			
Yes	Yes	No			
<b>Direct Food</b> No					
*Please contact your sales rep	presentative for details				

Last update: 08/21/2024

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com