

Pressure-sensitive adhesives

Acrylic

Paper

# PREMIUM OFFSET PERM -0-SCORE

#### **FACESTOCK**

This premium uncoated facestock features a 98% brightness, balanced white shade, superior opacity, and a smooth velvety feel.

Туре

Paper

PROPERTIES VALUE

**Basis Weight** 60# 25x38x500

Caliper 4.6 mil

**REGULATORY APPROVAL** 

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

FSC No

### **ADHESIVE**

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

Туре	Composition	Shear	
Permanent	Acrylic	350	

Min. Application Temperature Min. Service Temperature Max. Application Temperature

35 F -65 F 200 F

PROPERTIES		VALUE

Stainless Steel5.6 lbs/linear in.Glass2,8lbs/linear in.

Polyethylene 2.9

**Corrugated** 1.50 lbs./in.

Painted Metal 4.9 lbs/linear in.

**Loop Tack** 2.70 oz/in<sup>2</sup>

## **REGULATORY APPROVAL**

RoHSProp65REACHYesNoYes

<sup>\*</sup>Please contact your sales representative for details

Yes	<b>CPSIA</b> Yes	<b>Direct Food</b> No	
Indirect Food Yes			
*Please contact your sales rep	presentative for details		

### **LINER**

A bleached kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting and butt-cutting

withstand all conventional processing operations including die-cutting and butt-cutting.				
Туре				
719363				
Tear MD	Tear CD			
51 Grams	100 Grams			
DESCRIPTION	VALUE			
Basis Weight	69 Lbs/Rm			
Caliper	4.6 Mil			
REGULATORY APPROVAL				
RoHS	Prop65	REACH		
Yes	Yes	Yes		
TPCH	CPSIA	UL		
Yes	Yes	No		
Direct Food				
No				

Last update: 08/19/2024

\*Please contact your sales representative for details

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS: Beontag

6206 Wolf Creek Pike Trotwood, OH 45426

800-358-4448

orders.us@beontag.com