Pressure-sensitive adhesives

Acrylic Paper

Premium Offset / Perm / -0- Score Liner

ITEM #34

FACESTOCK

This premium uncoated facestock features a 98% brightness, balanced white shade, superior opacity, and a smooth velvety feel.

Type Paper			
PROPERTIES	VALUE		
Basis Weight	60# 25x38x500		
Caliper	4.6 mil		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA	UL	
Yes	Yes	No	
FSC			
No			
	resentative for details		

ADHESIVE

A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.

Type Permanent	Composition Acrylic	Shear 350
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 200 F
PROPERTIES	VALUE	
Stainless Steel	5.6 lbs/linear in.	
Glass	2,8lbs/linear in.	
Polyethylene	2.9	
Corrugated	1.50 lbs./in.	
Painted Metal	4.9 lbs/linear in.	
Loop Tack	2.70 oz/in ²	

RoHS	Prop65	REACH
Yes	No	Yes
трсн	CPSIA	Direct Food
Yes	Yes	No
Indirect Food Yes		

*Please contact your sales representative for details

LINER

A bleached kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing operations including die-cutting and butt-cutting.

Туре 9019086				
Tensile MD 51	Tensile CD O			
Tear MD 0	Tear CD 0			
DESCRIPTION	VALUE			
Basis Weight	72			
Caliper	4.6			
REGULATORY APPROVAL				
RoHS Yes	Prop65 Yes	REACH Yes		
трсн Yes	CPSIA Yes	UL No		
Direct Food No				
*Please contact your sales representative for details				

Last update: 08/21/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>