Pressure-sensitive adhesives Latex

Paper

TAMPER EVIDENT MATTE PAPER SPECIAL PERM 40#SCK

ITEM #11303

FACESTOCK

Type Paper				
Tensile MD	Tensile CD			
26 Lbs/in	18 Lbs/in			
Tear MD	Tear CD 42 Grams			
42 Grams				
PROPERTIES	VALUE			
Basis Weight	42 # Rm 24 x 26			
Caliper	2.70 Mil	2.70 Mil 87		
Opacity	87			
Brightness	86			
REGULATORY APPROVAL				
RoHS Yes	Prop65 Yes	REACH Yes		
ТРСН	CPSIA	UL		
Yes	Yes	No		
fsc No				

ADHESIVE

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Type Permanent	Composition Latex	Shear 80
Min. Application Temperature 35 F	Min. Service Temperature -65 F	Max. Application Temperature 220 F
PROPERTIES	VALUE	
PROPERTIES Stainless Steel	VALUE 7.3 lbs/linear in.	

Polyethylene	6.5			
Corrugated	2.50 lbs./in.			
Painted Metal	7.0 lbs/linear in.	7.0 lbs/linear in.		
Loop Tack	5.00 oz/in ²			
REGULATORY APPROVAL				
RoHS Yes	Prop65 No	REACH Yes		
трсн Yes	CPSIA Yes	Direct Food No		
Indirect Food Yes				
*Please contact your sales representative for details				

LINER

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Туре 5517342				
Tensile MD	Tensile CD			
34	22			
Tear MD	Tear CD			
32	34			
DESCRIPTION	VALUE			
Basis Weight	40			
Caliper	2.5			
oanper	2.0			
REGULATORY APPROVAL				
RoHS	Prop65	REACH		
Yes	Yes	Yes		
ТРСН	CPSIA	UL		
Yes	Yes	No		
Direct Food No				
*Please contact your sales representative for details				

Last update: 08/22/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com