

Pressure-sensitive adhesives

Acrylic

Paper

TECHNI-GLOSS II HIGH GLOSS / IP400 / 1.2 MIL PET L-3

ITEM #88453

FACESTOCK

A premium cast coated C1S white high gloss paper with a smooth print surface that offers excellent receptivity and print characteristics. The 90% gloss rating provides for the desired wet look label graphics that product manufacturers desire to enhance sales activity.

Type

Paper

Tensile MD Tensile CD 25 Lbs/in 0 Lbs/in Tear MD Tear CD 35 Grams 40 Grams

PROPERTIES VALUE

57 # Rm 24 x 26 **Basis Weight**

Caliper 3.70 Mil

Opacity 90 87

Brightness

REGULATORY APPROVAL

REACH **RoHS** Prop65 Yes Yes Yes **TPCH CPSIA** UL Yes No Yes

FSC No

ADHESIVE

A specialty adhesive designed to adhere to glass wine bottles with good ultimate adhesion when applied at temperatures as low as +35 F. Excellent permanency at room temperatures. Good plasticizer, UV & solvent resistance. Excellent adhesive for wet strength wine label facestocks when submersed in ice buckets.

Туре	Composition	Shear
Permanent	Acrylic	80

Min. Application Temperature Max. Application Temperature Min. Service Temperature

35 F -65 F 200 F

PROPERTIES	VALUE

Stainless Steel 5.5 lbs/linear in.

Glass 3,2lbs/linear in.

^{*}Please contact your sales representative for details

Polyethylene 2

Corrugated 1.45 lbs./in.

Painted Metal 3.0 lbs/linear in.

5.00 oz/in² **Loop Tack**

REGULATORY APPROVAL

RoHS Prop65 **REACH** Yes Yes Yes

TPCH CPSIA Direct Food

Yes Yes Nο

Indirect Food

Yes

*Please contact your sales representative for details

LINER

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Tensile CD Tensile MD

30000

Tear MD Tear CD 0 0

DESCRIPTION **VALUE**

0 **Basis Weight**

1,2 Caliper

REGULATORY APPROVAL

REACH RoHS Prop65 Yes Yes Yes

TPCH CPSIA Yes Yes

*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com