



Pressure-sensitive adhesives

Hot Melt

Techni-Therm Direct II TC / TP050 / 2.1 mil BG

ITEM #88515

<b>ADHESIVE</b> General purpose, strong permanent adhesive with good chill characteristics. TP050 has excellent initial tack with high bond strength at elevated, room and chilled temperatures, as well as in moist conditions. It has been formulated to adhere to a wide variety of substrates, including corrugated cardboard, low surface energy materials like polyethylene and non-polar surfaces. TP050 provides enhanced conversion characteristics, allowing die-cutting at higher speeds and is designed for both paper and synthetic face materials. Limitation: Not suitable for labelling plasticized.		
<b>Type</b> Permanent	<b>Composition</b> Hot Melt	<b>Min. Application Temperature</b> 23 F
<b>Min. Service Temperature</b> -40 F	<b>Max. Application Temperature</b> 158 F	
<b>REGULATORY APPROVAL</b>		
<b>RoHS</b> Yes	<b>Prop65</b> Yes	<b>REACH</b> Yes
<b>TPCH</b> Yes	<b>CPSIA</b> Yes	<b>UL</b> No
<b>Direct Food</b> No	<b>Indirect Food</b> Yes	
*Please contact your sales representative for details		

Last update: 08/21/2024

ADDRESS:  
Beontag  
6206 Wolf Creek Pike  
Trotwood, OH 45426  
[800-358-4448](tel:800-358-4448)  
[orders.us@beontag.com](mailto:orders.us@beontag.com)