

Pressure-sensitive adhesives

Latex

Techni-Therm Direct NTC / AP151 @ 1.3 CWT. / 1.2 Mil PET

ITEM #881247

FACESTOCK

A medium sensitivity, non-topcoated direct thermal label facestock designed for short-duration applications in dry environments. This paper has an initial activation temperature of 185°F and an effective activation temperature of 280°F. This product contains BPS which is known to the state of California to cause cancer, birth defects, or other reproductive harm (Prop 65).

Туре	
Paper	

Caliper

Tensile CD Tensile MD >21 11.5 lbs.in

PROPERTIES VALUE

47 lbs/rm **Basis Weight** 3.03 mil

REGULATORY APPROVAL

REACH RoHS Prop65 Yes No Yes **TPCH CPSIA** UL Yes No Yes

FSC No

ADHESIVE

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Type	Composition	Shear
Permanent	Latex	80
Min Application Temperature	Min Service Temperature	May Application Tempera

мах. Application Temperature Min. Service Temperature

35 F -65 F 220 F

PROPERTIES	VALUE

Stainless Steel 7.3 lbs/linear in. Glass 5.7 lbs/linear in.

Polyethylene 6.5

Corrugated 2.50 lbs./in.

Painted Metal 7.0 lbs/linear in.

^{*}Please contact your sales representative for details

Loop Tack	5.00 oz/in ²		
REGULATORY APPROVAL			
RoHS Yes	Prop65 No	REACH Yes	
TPCH Yes	CPSIA Yes	Direct Food No	
Indirect Food Yes			
*Please contact your sales re	presentative for details		

LINER			
An economical 1.2 mil clear p	olyester film liner good for an array of prim	e label applications.	
Tensile MD	Tensile CD		
30000	0		
Tear MD	Tear CD		
0	0		
DESCRIPTION	VALUE		
Basis Weight	0		
Caliper	1,2		
REGULATORY APPROVAL			
RoHS	Prop65	REACH	
Yes	Yes	Yes	
ТРСН	CPSIA		
Yes	Yes		
*Please contact your sales r			

Last update: 08/21/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com