



Pressure-sensitive adhesives

Latex

Paper

TECHNI-THERM DIRECT NTC / AP151 @ 1.3 Cwt. / 40#SCK L-3

ITEM #8852401

<b>FACESTOCK</b> A medium sensitivity, non-topcoated direct thermal label facestock designed for short-duration applications in dry environments. This paper has an initial activation temperature of 185°F and an effective activation temperature of 280°F. This product contains BPS which is known to the state of California to cause cancer, birth defects, or other reproductive harm (Prop 65).		
<b>Type</b> Paper		
<b>Tensile MD</b> >21	<b>Tensile CD</b> 11.5 lbs.in	
<b>PROPERTIES</b>		
<b>Basis Weight</b>	47 lbs/rm	
<b>Caliper</b>	3.03 mil	
<b>REGULATORY APPROVAL</b>		
<b>RoHS</b> Yes	<b>Prop65</b> No	<b>REACH</b> Yes
<b>TPCH</b> Yes	<b>CPSIA</b> Yes	<b>UL</b> No
<b>FSC</b> No		
*Please contact your sales representative for details		

<b>ADHESIVE</b> An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.		
<b>Type</b> Permanent	<b>Composition</b> Latex	<b>Shear</b> 80
<b>Min. Application Temperature</b> 35 F	<b>Min. Service Temperature</b> -65 F	<b>Max. Application Temperature</b> 220 F
<b>PROPERTIES</b>		
<b>VALUE</b>		
<b>Stainless Steel</b>	7.3 lbs/linear in.	
<b>Glass</b>	5.7 lbs/linear in.	
<b>Polyethylene</b>	6.5	
<b>Corrugated</b>	2.50 lbs./in.	
<b>Painted Metal</b>	7.0 lbs/linear in.	

<b>Loop Tack</b>			5.00 oz/in <sup>2</sup>
<b>REGULATORY APPROVAL</b>			
<b>RoHS</b> Yes	<b>Prop65</b> No	<b>REACH</b> Yes	
<b>TPCH</b> Yes	<b>CPSIA</b> Yes	<b>Direct Food</b> No	
<b>Indirect Food</b> Yes			
*Please contact your sales representative for details			

<b>LINER</b>			
A super calendered kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.			
<b>Type</b> 5517342			
<b>Tensile MD</b> 30 Lbs/In	<b>Tensile CD</b> 20 Lbs/In		
<b>Tear MD</b> 32 Grams	<b>Tear CD</b> 34 Grams		
<b>DESCRIPTION</b>	<b>VALUE</b>		
<b>Basis Weight</b>	40.5 Lbs/Rm		
<b>Caliper</b>	2.5 Mil		
<b>REGULATORY APPROVAL</b>			
<b>RoHS</b> Yes	<b>Prop65</b> Yes	<b>REACH</b> Yes	
<b>TPCH</b> Yes	<b>CPSIA</b> Yes	<b>UL</b> No	
<b>Direct Food</b> No			
*Please contact your sales representative for details			