

Pressure-sensitive adhesives

Acrylic

Paper

TECHNI-THERM DIRECT NTC / TR1 @ 1.0 Cwt. / 40#SCK L-3

ITEM #8819141

FACESTOCK

A medium sensitivity, non-topcoated direct thermal label facestock designed for short-duration applications in dry environments. This paper has an initial activation temperature of 185°F and an effective activation temperature of 280°F. This product contains BPS which is known to the state of California to cause cancer, birth defects, or other reproductive harm (Prop 65).

Type Paper

Tensile MD Tensile CD >21 11.5 lbs.in

PROPERTIES VALUE

Basis Weight 47 lbs/rm
Caliper 3.03 mil

REGULATORY APPROVAL

 RoHS
 Prop65
 REACH

 Yes
 No
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No

FSC No

ADHESIVE

A specialty acrylic adhesive designed for clean removability from plastics and painted metal. Not recommended for curved or textured surfaces.

TypeCompositionShearRemovableAcrylic35

Min. Application Temperature Min. Service Temperature Max. Application Temperature

120 F

40 F -65 F

PROPERTIES VALUE

Stainless Steel 1.8 lbs/linear in.

Glass 0lbs/linear in.

Corrugated 0.55 lbs./in.

Painted Metal 1.3 lbs/linear in.

Loop Tack 1.35 oz/in²

^{*}Please contact your sales representative for details

REGULATORY APPROVAL

RoHSProp65REACHYesYesYes

TPCH CPSIA Direct Food

Yes Yes

Indirect Food

Yes

*Please contact your sales representative for details

LINER

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

No

Туре

5517342

Tensile MD Tensile CD

34 22

 Tear MD
 Tear CD

 32
 34

DESCRIPTION VALUE

Caliper 2.5

REGULATORY APPROVAL

Basis Weight

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

40

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com

^{*}Please contact your sales representative for details