

Pressure-sensitive adhesives

Latex

Paper

TECHNI-THERM DIRECT NTC / TR447 / 40#SCK SP LINER

ITEM #2871311

FACESTOCK

A medium sensitivity, non-topcoated direct thermal label facestock designed for short-duration applications in dry environments. This paper has an initial activation temperature of 185°F and an effective activation temperature of 280°F. This product contains BPS which is known to the state of California to cause cancer, birth defects, or other reproductive harm (Prop 65).

Type Paper

Tensile MD Tensile CD >21 11.5 lbs.in

PROPERTIES VALUE

Basis Weight 47 lbs/rm 3.03 mil Caliper

REGULATORY APPROVAL

REACH RoHS Prop65 Yes No Yes **TPCH CPSIA** UL Yes Yes No

FSC No

ADHESIVE

A general purpose, removable rubber based emulsion adhesive featuring good initial tack and moderate adhesion. It has limited plasticizer, UV and solvent resistance. This is a standard removable adhesive for tape reels, computer disks and kids stickers.

Composition Shear Removable Latex 40

Min. Application Temperature Min. Service Temperature Max. Application Temperature 40 F 1 F

120 F

PROPERTIES VALUE

Stainless Steel 2.5 lbs/linear in.

Glass 0,9lbs/linear in.

Polyethylene 1,8

1.00 lbs./in. Corrugated

Painted Metal 1.6 lbs/linear in.

Loop Tack 1.50 oz/in²

^{*}Please contact your sales representative for details

REGULATORY APPROVAL

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

*Please contact your sales representative for details

LINER

A super calendared kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.

Туре

5517342

Tensile MDTensile CD30 Lbs/In20 Lbs/In

Tear MDTear CD32 Grams34 Grams

DESCRIPTION VALUE

Basis Weight 40.5 Lbs/Rm

Caliper 2.5 Mil

REGULATORY APPROVAL

RoHSProp65REACHYesYesYes
TPCH
Yes
CPSIA
Yes
No

Direct Food

No

*Please contact your sales representative for details

Last update: 08/21/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com