

TECHNI-THERM SP TL250 50#SCK L-2

ITEM #73059

FACESTOCK A coated one side thermal transfer facestock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This facestock also offers an 86% brightness and an 87% opacity.		
Type Paper		
Tensile MD 26 Lbs/in	Tensile CD 18 Lbs/in	
Tear MD 42 Grams	Tear CD 42 Grams	
PROPERTIES		
VALUE		
Basis Weight	42 # Rm 24 x 26	
Caliper	2.70 Mil	
Opacity	87	
Brightness	86	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
FSC No		
*Please contact your sales representative for details		

ADHESIVE An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.		
Type Permanent		
Composition Rubber		
PROPERTIES		
VALUE		
Glass	6,7lbs/linear in.	
Polyethylene	7,5	
REGULATORY APPROVAL		

RoHS Yes	Prop65 No	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No	Indirect Food Yes	
*Please contact your sales representative for details		

LINER

A paper liner that has been silicone coated one side to give a controlled release. This paper has a hard smooth caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type 5517543		
Tensile MD 43 Lbs/In	Tensile CD 27 Lbs/In	
Tear MD 44 Grams	Tear CD 48 Grams	
DESCRIPTION	VALUE	
Basis Weight	52.3 Lbs/Rm	
Caliper	3.2 mil	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No		
*Please contact your sales representative for details		

Last update: 08/22/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com