

Pressure-sensitive adhesives Acrylic

Film

WHITE BOPP DT / TR1 @ 1.0 Cwt. / 40#SCK L-3

ITEM #86103

FACESTOCK

A white topcoated synthetic, thermal label facestock with exceptional smoothness. This lightweight product has high durability and exceptional yield, as well as environmental and water resistance.

Туре Film

Tensile MD Tensile CD 5.2 13.5 **Elong MD Elong CD** 220 38

PROPERTIES VALUE

4.0 Mil Caliper

REGULATORY APPROVAL

RoHS Prop65 **REACH** Yes No Yes **TPCH CPSIA FSC** Yes Yes No

ADHESIVE

A specialty acrylic adhesive designed for clean removability from plastics and painted metal. Not recommended for curved or textured surfaces.

Type Composition Shear Removable Acrylic 35

Min. Application Temperature Min. Service Temperature Max. Application Temperature 120 F

40 F -65 F

PROPERTIES VALUE

Stainless Steel 1.8 lbs/linear in. **Glass** 0lbs/linear in.

Corrugated 0.55 lbs./in.

Painted Metal 1.3 lbs/linear in.

1.35 oz/in² **Loop Tack**

REGULATORY APPROVAL

^{*}Please contact your sales representative for details

REACH RoHS Prop65 Yes Yes Yes **TPCH CPSIA Direct Food**

Yes

Indirect Food

Yes

Yes

LINER

A super calendared kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.

No

Type 5517342 **Tensile MD Tensile CD** 30 Lbs/In 20 Lbs/In

Tear MD Tear CD 34 Grams 32 Grams

DESCRIPTION VALUE

Basis Weight 40.5 Lbs/Rm

Caliper 2.5 Mil

REGULATORY APPROVAL

REACH Prop65 **RoHS** Yes Yes Yes **TPCH CPSIA** UL No Yes Yes

Direct Food

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

^{*}Please contact your sales representative for details

^{*}Please contact your sales representative for details