

Pressure-sensitive adhesives

Acrylic

Film

# WHITE BOPP DT / TS583 @ 2.10 Cwt. / 40#SCK L-3

## ITEM #86100

## **FACESTOCK**

A white topcoated synthetic, thermal label facestock with exceptional smoothness. This lightweight product has high durability and exceptional yield, as well as environmental and water resistance.

Туре Film

**Tensile MD Tensile CD** 5.2 13.5 **Elong CD Elong MD** 220 38

**PROPERTIES** VALUE

4.0 Mil Caliper

**REGULATORY APPROVAL** 

**RoHS** Prop65 **REACH** Yes No Yes **TPCH CPSIA FSC** Yes Yes No

# **ADHESIVE**

A specialty adhesive designed to adhere to hard to label surfaces with excellent ultimate adhesion when applied at temperatures as low as -20 F. Outstanding permanency at room temperatures. This adhesive has good plasticizer, UV & solvent resistance and high initial tack.

Shear Composition Type Acrylic 70 Permanent

Min. Application Temperature Min. Service Temperature Max. Application Temperature -20 F

-65 F 160 F

**PROPERTIES VALUE** 

**Stainless Steel** 5.9 lbs/linear in.

**Glass** 4,2lbs/linear in.

6,5lbs/linear in. **Polyethylene** 

Corrugated 1.50 lbs./in.

**Painted Metal** 5.1 lbs/linear in.

**Loop Tack** 3.20 oz/in<sup>2</sup>

<sup>\*</sup>Please contact your sales representative for details

#### **REGULATORY APPROVAL**

RoHSProp65REACHYesNoYes

TPCH CPSIA Direct Food

Yes Yes No

**Indirect Food** 

Yes

\*Please contact your sales representative for details

## **LINER**

A super calendared kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.

Туре

5517342

 Tensile MD
 Tensile CD

 30 Lbs/In
 20 Lbs/In

 Tear MD
 Tear CD

 32 Grams
 34 Grams

**DESCRIPTION** VALUE

Basis Weight 40.5 Lbs/Rm

Caliper 2.5 Mil

### **REGULATORY APPROVAL**

 RoHS
 Prop65
 REACH

 Yes
 Yes
 Yes

 TPCH
 CPSIA
 UL

 Yes
 No
 No

**Direct Food** 

No

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com

<sup>\*</sup>Please contact your sales representative for details