

Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives

Special Permanent @ 1.70 Cwt.

ADHESIVE

An aggressive rubber based adhesive showing high initial tack with high shear and high ultimate adhesion. It has fair plasticizer, UV and solvent resistance. This is not recommended for water immersion. This adhesive has good adhesion to most substrates.

Composition Shear Type Permanent 155 Latex

Min. Application Temperature Min. Service Temperature Max. Application Temperature 35 F 200 F

65 F

PROPERTIES VALUE

Stainless Steel 5.8 lbs/linear in.

Glass 2,8lbs/linear in.

5.6 **Polyethylene**

Corrugated 2.70 lbs./in.

5.4 lbs/linear in. **Painted Metal**

4.20 oz/in² Loop Tack

REGULATORY APPROVAL

REACH RoHS Prop65 Yes Yes Yes

TPCH CPSIA Direct Food

Yes No Yes

Indirect Food

Yes

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com

^{*}Please contact your sales representative for details