

Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives Acrylic

TP160 @ 1.30 Cwt. / TP160 @ 1.30 Cwt.

ADHESIVE

An improved general purpose acrylic adhesive showing good initial tack, shear, and high ultimate adhesion. It has a good plasticizer, UV and solvent resistance, as well as compostability. This adhesive also displays excellent die-cutting and stripping traits & has excellent adhesion to many different substrates, with an application temperature of +25 °F.

Type Composition Shear Permanent Acrylic 79

Min. Application Temperature Min. Service Temperature Max. Application Temperature

25 F -65 F 200 F

PROPERTIES VALUE

Stainless Steel 6.8 lbs/linear in.

Glass 0lbs/linear in.

Polyethylene 6.5

1.20 lbs./in. Corrugated

Painted Metal 6.4 lbs/linear in.

Loop Tack 2.90 oz/in²

REGULATORY APPROVAL

RoHS Prop65 **REACH** Yes Yes Yes

TPCH CPSIA Direct Food

Yes Yes No

Indirect Food

Yes

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448

orders.us@beontag.com

^{*}Please contact your sales representative for details