

Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives

Acrylic

TR445A

ADHESIVE

A specialty acrylic adhesive showing good to low initial tack with low shear and outstanding removable adhesion with good clarity and minimum cold flow. Excellent removability on a wide range of substrates. Not recommended for curved or textured surfaces.

Type Removable Min. Application Temperature 25 F	Composition Acrylic Min. Service Temperature 0 F	Shear 0 Max. Application Temperature 120 F
Stainless Steel	1.7 lbs/linear in.	
Glass	0	
Polyethylene	0.9	
Painted Metal	1.3 lbs/linear in.	
REGULATORY APPROVAL		
RoHS	Prop65	REACH
Yes	Yes	Yes
ТРСН	CPSIA	Direct Food
Yes Indirect Food	Yes	No
man ect 100a		

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:

Yes

Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 800-358-4448 orders.us@beontag.com

*Please contact your sales representative for details