Not a Current Stock Product

Please contact our team for assistance.

Pressure-sensitive adhesives Acrylic

Film

Tyvek / TS583 @ 2.50 Cwt.

FACESTOCK

A durable sheet that is stronger than paper, less expensive and more versatile than fabrics. It is made from high density polyethylene fibers and is considered a spunbonded olefin offering a balance of physical characteristics likened to a paper, film and cloth.

Type Film		
Tensile MD 42 Lbs/in	Tensile CD 48 Lbs/in	
Tear MD 453 Grams	Tear CD 453 Grams	
Elong MD 20	Elong CD 24	
PROPERTIES	VALUE	
Caliper	8.00 Mil	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	FSC No
*Please contact your sales representative	o for details	

ADHESIVE

A specialty adhesive designed to adhere to hard to label surfaces with excellent ultimate adhesion when applied at temperatures as low as -20 F. Outstanding permanency at room temperatures. This adhesive has good plasticizer, UV & solvent resistance and high initial tack.

Type Permanent	Composition Acrylic	Shear 70
Min. Application Temperature -20 F	Min. Service Temperature -65 F	Max. Application Temperature 160 F
PROPERTIES	VALUE	
PROPERTIES Stainless Steel	VALUE 6.1 lbs/linear in.	

Polyethylene	6,5lbs/linear in.	6,5lbs/linear in.		
Corrugated	1.50 lbs./in. 5.3 lbs/linear in. 3.20 oz/in²			
Painted Metal				
Loop Tack				
REGULATORY APPROVAL				
RoHS	Prop65	REACH		
Yes	No	Yes		
трсн	CPSIA	Direct Food		
Yes	Yes	No		
Indirect Food				

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG's standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG's shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS: Beontag 6206 Wolf Creek Pike Trotwood, OH 45426 <u>800-358-4448</u> <u>orders.us@beontag.com</u>