

Not a Current Stock Product

Please contact our team for assistance.

- Pressure-sensitive adhesives
- Acrylic

Ultra-Removable Adhesive

ADHESIVE An ultra-removable emulsion acrylic adhesive with low tack on smooth flat surfaces that can be cleanly removed after extended periods of time. This adhesive is suitable for glass, counter tops, painted metal, smooth painted walls, and stainless steel. This adhesive should be qualified for end-use suitability.		
Type Removable	Composition Acrylic	
PROPERTIES	VALUE	
Glass	0.3 lbs/linear in.	
Polyethylene	6,5lbs/linear in.	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No	Indirect Food Yes	FDA 21 CFR 175.105, BfR XIV No
*Please contact your sales representative for details		

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

ADDRESS:
Beontag
6206 Wolf Creek Pike
Trotwood, OH 45426
[800-358-4448](tel:800-358-4448)
orders.us@beontag.com