

Pressure-sensitive adhesives

Rubber

Film

# 4 MIL YELLOW VINYL / TL250 @ 2.5 Cwt. / 50#SCK L-3

ITEM #84878

## Facestock

A 4 mil yellow vinyl face sheet with consistent lay flat and gauge control for high tech label application. Polymeric plasticizers formulated to provide optimum performance with pressure sensitive adhesives.

### Type

Film

### Tensile MD

3300 lb/in

### Tensile CD

2900 lb/in

### Elong MD

100

### Elong CD

150

### Properties

### Value

### Caliper

4

## Regulatory Approval

### RoHS

Yes

### Prop65

Yes

### REACH

Yes

### TPCH

Yes

### CPSIA

Yes

### FSC

No

\*Please contact your sales representative for details

## Adhesive

An outstanding general purpose permanent adhesive which has high initial tack and high ultimate adhesion. It is used for tire label and many other difficult to label substrates.

### Composition

Rubber

### Type

Permanent

## Typical Adhesion values

### Properties

### Value

### Glass

6.0

### Polyethylene

7.0

## Regulatory Approval

**RoHS**

Yes

**Prop65**

Yes

**REACH**

Yes

**TPCH**

Yes

**CPSIA**

Yes

**UL**

No

**Direct Food**

No

**Indirect Food**

Yes

**FDA 21 CFR 175.105, BfR XIV**

No

\*Please contact your sales representative for details

**Liner**

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

**Type**

5517353

**Tensile MD**

40 Lbs/In

**Tensile CD**

24 Lbs/In

**Tear MD**

44 Grams

**Tensile CD**

48 Grams

**Description****Value****Basis Weight**

50 Lbs/Rm

**Caliper**

3.2 Mil

**Regulatory Approval****RoHS**

Yes

**Prop65**

Yes

**REACH**

Yes

**TPCH**

Yes

**CPSIA**

Yes

**UL**

No

**Direct Food**

No

\*Please contact your sales representative for details

Last update: 05/01/2024

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

**ADDRESS:**

Beontag

222 Mound Avenue Miamisburg, OH 45342

[800-358-4448](tel:800-358-4448)[orders.us@beontag.com](mailto:orders.us@beontag.com)