

Not a Current Stock Product

Please contact our team for assistance.

Self adhesives

Latex

Film

1 Mil Dull Silver TC Polyester / AP151 1.7 CWT / 1.2 MIL PET

FACESTOCK

This versatile top-coating is compatible with solvent base, water base, and UV curable inks, as well as silk screen, flexographic and offset/letterpress printing.

Type

Film

Tensile MD

28000 Psi

Tensile CD

34000 Psi

Tear MD

1400 Grams

Elong MD

300

Elong CD

110

PROPERTIES

VALUE

Caliper

1.00 Mil

REGULATORY APPROVAL

Prop65

Yes

FSC

No

ADHESIVE

An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.

Type

Permanent

Shear

80

Min. Application Temperature

35°C

Min. Service Temperature

-65°C

Max. Service Temperature

220°C

PROPERTIES

VALUE

Stainless Steel

7.7 lbs/linear in.

Typical Peel Adhesion

5,7 lbs/linear in.

Polyethylene

6.5

Corrugated

2.90 lbs./in.

Painted Metal

7.4 lbs/linear in.

Loop Tack

5.40 oz/in²

REGULATORY APPROVAL

RoHS
Yes

Prop65
No

REACH
Yes

TPCH
Yes

CPSIA
Yes

Direct Food
No

Indirect Food
Yes

BACKING

An economical 1.2 mil clear polyester film liner good for an array of prime label applications.

Type

716666

Tensile MD
30000

Tensile CD
0

Tear MD
0

Tear CD
0

DESCRIPTION

VALUE

Caliper

1.2

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com