

Not a Current Stock Product

Please contact our team for assistance.

- Self adhesives
- Latex
- Film

1 mil White TC Polyester / AP151 Opaque @ 1.70 Cwt. / 1.5 Mil Clear Polyester L-3

FACESTOCK	
This 1 mil white top-coated polyester face provides excellent UV resistance and durability for a number of applications. The versatile top-coating is compatible with solvent base, water base and UV curable inks, as well as silk screen, flexographic and offset/letterpress printing.	
Type Film	
Elong MD 110	Elong CD 90
PROPERTIES	VALUE
Basis Weight	1
Caliper	1.00 Mil
REGULATORY APPROVAL	
Prop65 Yes	FSC No

ADHESIVE		
An outstanding general purpose permanent opaque adhesive that has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting and stripping traits. Provides opacity for cover up applications.		
Type	Shear	Min. Application Temperature
Permanent	80	35°C
Min. Service Temperature	Max. Service Temperature	
-65°C	220°C	
PROPERTIES	VALUE	
Stainless Steel	7.7 lbs/linear in.	
Typical Peel Adhesion	5,7 lbs/linear in.	
Polyethylene	6,5	
Corrugated	2.90 lbs./in.	
Painted Metal	7.4 lbs/linear in.	
Loop Tack	5.40 oz/in²	

REGULATORY APPROVAL**RoHS**

Yes

Prop65

No

REACH

Yes

TPCH

Yes

CPSIA

Yes

Direct Food

No

Indirect Food

Yes

BACKING

A 1.5 mil polyester liner which has been silicone coated one side to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end-usage, making it an outstanding liner for high speed, automatic applications.

Tensile MD

33000

Tensile CD

0

Tear MD

0

Tear CD

0

DESCRIPTION**VALUE****Basis Weight**

0

Caliper

1,5

REGULATORY APPROVAL**RoHS**

Yes

Prop65

Yes

REACH

Yes

TPCH

Yes

CPSIA

Yes

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com