

Not a Current Stock Product

Please contact our team for assistance.

- Self adhesives
- Acrylic
- Film

1.7 Mil Clear Acetate / ALL TEMP / 0.94 MIL PET

FACESTOCK A 1.7 mil clear film with excellent ink receptivity and printability.		
Type Film		
Tensile MD 12,500 psi		
Tear MD 9 grams		
PROPERTIES		VALUE
Caliper		1.7 mil
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
FSC No		

ADHESIVE An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Excellent permanency at room temperatures. Very good plasticizer, UV and solvent resistance. This adhesive offers a neutral ph level (Acid Free)		
Type Permanent	Shear 100	Min. Application Temperature -20°C
Min. Service Temperature -65°C	Max. Service Temperature 160°C	
PROPERTIES		VALUE
Stainless Steel		5.1 lbs/linear in.
Typical Peel Adhesion		4,4 lbs/linear in.
Polyethylene		4.2
Corrugated		1.50 lbs./in.
Painted Metal		

4.9 lbs/linear in.

Loop Tack

2.90 oz/in²

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

Direct Food
Yes

Indirect Food
Yes

BACKING

An economical.94 mil clear polyester film liner good for an array of prime label applications.

Type
colacril liner

DESCRIPTION

VALUE

Caliper

0.94 mil

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:
Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50
orders.scandstick@beontag.com