

Not a Current Stock Product

Please contact our team for assistance.

- Self adhesives
- Acrylic
- Film

4 mil Soft White Vinyl / TS523 @ 1.00 Cwt. / 8 PT Tag Liner L-3

FACESTOCK A 4 mil flexible white vinyl with polymeric plasticizers, formulated to provide optimum performance with pressure sensitive adhesives. The top-coating provides outstanding adhesion to various printing inks.		
Type Film		
Tensile MD 3900	Tensile CD 3800	
Tear MD 100	Tear CD 100	
PROPERTIES		
Caliper	4.0	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	FSC No

ADHESIVE A tri-bonded specialty clear acrylic adhesive featuring high initial tack, high shear & high ultimate adhesion with excellent clarity and minimum cold flow. It has outstanding plasticizer, UV, solvent and occasional water and oil resistance. This is an acid free adhesive.		
Type Permanent	Shear 110	Min. Application Temperature 35°C
Min. Service Temperature -65°C	Max. Service Temperature 180°C	
PROPERTIES	VALUE	
Stainless Steel	4.7 lbs/linear in.	
Typical Peel Adhesion	2,8lbs/linear in.	
Polyethylene	2.9	
Corrugated	1.20 lbs./in.	
Painted Metal	4.2 lbs/linear in.	

Loop Tack

1.70 oz/in²

REGULATORY APPROVAL

RoHS
Yes

Prop65
No

REACH
Yes

TPCH
Yes

CPSIA
Yes

Direct Food
No

Indirect Food
Yes

BACKING

An 8pt, 100# tag liner which has been silicone coated one side to give a controlled release. It has exceptionally high internal strength to withstand all conventional processing operations including die-cutting, perforating, fanfolding and refolding processes.

Type
17380

Tensile MD
63

Tensile CD
34

Tear MD
149

Tear CD
156

DESCRIPTION

VALUE

Basis Weight

102

Caliper

8

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:
Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50
orders.scandstick@beontag.com