

# Not a Current Stock Product

Please contact our team for assistance.

**Self adhesives**   **Liner**

## 42# L-30 SILICONE LINER

<b>FACESTOCK</b> CCK liner which has been silicone coated one side to give a controlled release. This paper has a hard smooth caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing. Can be silicone coated 1 or 2 sides.	
<b>Type</b> Liner	
<b>Tensile MD</b> 34# /	<b>Tensile CD</b> 22# / Inch
<b>Tear MD</b> 32 Grams 2	<b>Tear CD</b> 34 Grams 2
<b>PROPERTIES</b>	<b>VALUE</b>
<b>Basis Weight</b>	40.7#/ Ream (24x36-500)
<b>Caliper</b>	2.5 Mills
<b>REGULATORY APPROVAL</b>	
<b>Prop65</b> Yes	<b>FSC</b> No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

**ADDRESS:**

Beontag  
Pål Anders väg 4, 263 35  
Höganäs, Sweden  
+46 42 25 00 50

[orders.scandstick@beontag.com](mailto:orders.scandstick@beontag.com)