

Not a Current Stock Product

Please contact our team for assistance.

- Self adhesives
- Latex
- Paper

50# C1S SEMIGLOSS / AP151 Opaque @ 2.10 Cwt. / 40#SCK L-3

<div>FACESTOCK</div> <div>A semi-gloss facestock designed for applications requiring premium label appearance and excellent flexographic printing. This face features great brightness and high opacity with a gloss finish for excellent print fidelity and over-lamination adhesion and high strength required for fast matrix stripping and runnability.</div>		
<div>Type</div> <div>Paper</div>		
<div>Tensile MD</div> <div>30</div>	<div>Tensile CD</div> <div>12</div>	
<div>Tear MD</div> <div>38</div>	<div>Tear CD</div> <div>42</div>	
<div>PROPERTIES</div> <div>VALUE</div>		
<div>Basis Weight</div> <div>Caliper</div>	<div>47</div> <div>2.3 mil</div>	
<div>REGULATORY APPROVAL</div>		
<div>RoHS</div> <div>Yes</div>	<div>Prop65</div> <div>Yes</div>	<div>REACH</div> <div>Yes</div>
<div>TPCH</div> <div>Yes</div>	<div>CPSIA</div> <div>Yes</div>	<div>FSC</div> <div>No</div>
<div>ADHESIVE</div> <div>An outstanding general purpose permanent opaque adhesive that has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting and stripping traits. Provides opacity for cover up applications.</div>		
<div>Type</div> <div>Permanent</div>	<div>Shear</div> <div>0</div>	<div>Min. Application Temperature</div> <div>25°C</div>
<div>Min. Service Temperature</div> <div>-65°C</div>	<div>Max. Service Temperature</div> <div>220°C</div>	
<div>PROPERTIES</div> <div>VALUE</div>		
<div>Typical Peel Adhesion</div> <div>Polyethylene</div>	<div>5,7 lbs/linear in.</div> <div>6.5</div>	

REGULATORY APPROVAL

RoHS
Yes

Prop65
No

REACH
Yes

TPCH
Yes

CPSIA
Yes

Direct Food
No

Indirect Food
Yes

BACKING

Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.

Type
5517342

Tensile MD
34

Tensile CD
22

Tear MD
32

Tear CD
34

DESCRIPTION

VALUE

Basis Weight

40

Caliper

2.5

REGULATORY APPROVAL

RoHS
Yes

Prop65
Yes

REACH
Yes

TPCH
Yes

CPSIA
Yes

UL
No

Direct Food
No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden

+46 42 25 00 50

orders.scandstick@beontag.com