

Not a Current Stock Product

Please contact our team for assistance.

- Self adhesives
- Acrylic
- Paper

55# DTC Hibright Semigloss / AT150 / 40#SCK L-3

FACESTOCK A premium semigloss calendar coated one side stock with a top coating for digital toner printing. It also offers good flexibility and high internal strength for ease in converting .	
Type Paper	
Tensile MD 30 Lbs/in	Tensile CD 20 Lbs/in
Tear MD 50 Grams	Tear CD 55 Grams
PROPERTIES	VALUE
Basis Weight	55
Caliper	2.80 Mil
Opacity	87
Brightness	88
REGULATORY APPROVAL	
Prop65 Yes	FSC No

ADHESIVE An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Very good plasticizer, UV and solvent resistance. AT150 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps		
Type Permanent	Shear 105	Min. Application Temperature -20°C
Min. Service Temperature -65°C	Max. Service Temperature 160°C	
PROPERTIES	VALUE	
Stainless Steel	5.4 lbs/linear in.	
Typical Peel Adhesion	4.4 lbs/linear in.	
Polyethylene	4.2	

Corrugated	1.50 lbs./in.	
Painted Metal	5.2 lbs/linear in.	
Loop Tack	3.00 oz/in ²	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	Direct Food Yes
Indirect Food Yes		

BACKING		
Supercalendered Kraft (SCK) liner which has been silicone coated one side to give a controlled release. This paper has a smooth, caliper consistent surface. Due to its high internal strength it will withstand all conventional processing operations including die-cutting, butt cutting, line scoring and dispensing.		
Type 5517342		
Tensile MD 34	Tensile CD 22	
Tear MD 32	Tear CD 34	
DESCRIPTION		
Basis Weight	40	
Caliper	2.5	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No		

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:
 Beontag
 Pål Anders väg 4, 263 35
 Höganäs, Sweden
 +46 42 25 00 50
orders.scandstick@beontag.com