

Not a Current Stock Product

Please contact our team for assistance.

Self adhesives

Acrylic Paper

60# Ultra White Semigloss / AT150 @ 1.4 Cwt. / 2.5 mil SCK L-3

FACESTOCK

A premium coated one side stock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This face offers a 90% Brightness and an 88% opacity.

Туре Paper

Tensile MD Tensile CD 35 Lbs/in 19 Lbs/in Tear MD Tear CD 47 Grams 46 Grams

PROPERTIES VALUE

Basis Weight 60 # Rm 25 x 38

Caliper 3.20 Mil

Opacity 88 90 **Brightness**

REGULATORY APPROVAL

RoHS REACH Prop65 Yes Yes Yes **TPCH CPSIA FSC** Yes Yes No

ADHESIVE

An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Very good plasticizer, UV and solvent resistance. AT150 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps

Туре

Permanent

PROPERTIES	VALUE
Typical Peel Adhesion	4.4 lbs/linear in.
Polyethylene	4.2

REGULATORY APPROVAL		
RoHS	Prop65	REACH
Yes	Yes	Yes
TPCH	CPSIA	Direct Food
Yes	Yes	No
Indirect Food Yes		

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:

Beontag Pål Anders väg 4, 263 35 Höganäs, Sweden +46 42 25 00 50

orders.scandstick@beontag.com