

Not a Current Stock Product

Please contact our team for assistance.

Self adhesives Latex

AP151 @ 2.50 Cwt. / 1.5 MIL CLEAR PET LINER L-3 / L-25X / 1.5 MIL CLEAR PET LINER L-5

ADHESIVE An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.		
Type Permanent	Shear 80	Min. Application Temperature 35°C
Min. Service Temperature -65°C	Max. Service Temperature 220°C	
PROPERTIES	VALUE	
Stainless Steel	7.8 lbs/linear in.	
Typical Peel Adhesion	5,7 lbs/linear in.	
Polyethylene	6,5	
Painted Metal	7.5 lbs/linear in.	
REGULATORY APPROVAL		
RoHS Yes	Prop65 No	REACH Yes
CPSIA Yes	UL Yes	Direct Food No
Indirect Food Yes		

BACKING A 1.5 mil polyester liner which has been silicone coated on two sides to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end usage, making it an outstanding liner for high speed, automatic applications.	
Type 18129	
Tensile MD 32000	Tensile CD 0
Tear MD 0	Tear CD 0
DESCRIPTION	VALUE

Caliper	1.5	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No		

BACKING		
A 1.5 mil polyester liner which has been silicone coated on one side to give a controlled release. It has extremely high internal strength for ease in manufacturing, converting and end usage, making it an outstanding liner for high speed, automatic applications.		
Type 18109		
Tensile MD 32000	Tensile CD 0	
Tear MD 0	Tear CD 0	
DESCRIPTION	VALUE	
Caliper	1.5	
REGULATORY APPROVAL		
RoHS Yes	Prop65 Yes	REACH Yes
TPCH Yes	CPSIA Yes	UL No
Direct Food No		

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products.

ADDRESS:
 Beontag
 Pål Anders väg 4, 263 35
 Höganäs, Sweden
 +46 42 25 00 50
orders.scandstick@beontag.com