

FSC ScandTag TC 12X MA



FACESTOCK

ScandTag TC 12X MA is a white woodfree card, coated with thermosensitive coating (black imaging) and - topcoating. It has a good resistance to moisture, oil, fat, alcohol et.c. - ScandTag TC 12X MA can be printed using water based and UV inks and varnishes, designed for use with - direct thermal label papers.. - This thermosensitive product is designed for thermal print speeds up to 200 mm/s, depending on printer set up. - Reverse side is not suitable for high quality printing (half-tone et.c.) - It is recommended that customers assess both the pre-print and the overprint characteristics under end use - conditions before proceeding to long runs.

Type

Paper

Top Coating

Yes

Image color

Black

Printing speed (Max.)

200mm/s

PROPERTIES

METHOD

VALUE

Basis Weight

ISO 536

121 ± 12g/m²

Caliper

ISO 534

129 ± 15µ

Brightness

ISO 2470 (R457-)

> 80%

Smoothness

ISO 5627 (Bekk)

> 200s

REGULATORY APPROVAL

FSC

Yes

FINAL PRODUCT

Format

Roll

Certificate

The product is registered to SAI-COC-010567 FSC™ Mix credit.

Material Shelf Life

Min. 2 years, stored at 20°C/50% RH - N.B.: When labels are exposed to very high humidity conditions and are in direct contact with the packaging, it is - essential that appropriate water resistant varnish is used to prevent surface picking.

SKU

FTC12XM

Replaces all previous information.

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com