

ScandTag NTC PPF W

FACESTOCK

ScandTag NTC PPF W is a white, woodfree paper, with black imaging thermosensitive coating, laminated - together with a white foamed polypropylene film (backside). Despite the low density, the film has a good tear - resistance due to the monoaxially orientation. - It is designed for short term use in relatively clean and dry environments, where there are no requirements for - surface protection against contaminants or scruffing. - It can be printed with all commonly used technologies for roll converting, including water and uv-based flexo, uv - letterpress et.c., if inks and varnishes designed for direct thermal paper is used. - We recommend customers to assess both pre-print and thermal print characteristics under end-use conditions - before proceeding to long runs. - Typical use are labels and carry handles ("wine glass labels") for the food industry and other consumer goods. - This product does not contain Bisphenol A.

Type

Paper

Image color

Black

PROPERTIES**METHOD****VALUE****Basis Weight**

ISO 536

146g/m²**Caliper**

ISO 534

200μ

Smoothness

Bendtsen

35ml/min

REGULATORY APPROVAL**BPA Free**

Yes

FINAL PRODUCT

Format

Roll

Material Shelf Life

Min. 2 years, stored at 20°C/50% RH

SKU

205099E0T518

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com