

ScandTag SynTherm 17XMA

FACESTOCK

ScandTag Syntherm 17XMA is a top-coated, smudgeproof, chemi-thermal polypropylene based film. - It can be printed by water/solvent based, UV inks and varnishes. - This thermal product has a standard sensitivity making it suitable for print speeds up to 200-250mm per second - depending on printer settings. - It is recommended that customers assess both the pre-print and the overprint characteristics under end use - conditions before proceeding to long runs.

Type

Film

Printing speed (Max.)

200 - 250mm/s

PROPERTIES**METHOD****VALUE****Basis Weight**

ISO 536

143 ± 6g/m²**Caliper**

ISO 534

174 ± 12μ

Brightness

ISO 2470 (R457-)

> 90%

FINAL PRODUCT

Format

Roll

Material Shelf Life

Min. 2 years, stored at 20°C/50% RH - N.B.: When labels are exposed to very high humidity conditions and are in direct contact with the packaging, it is - essential that appropriate water resistant varnish is used to prevent surface picking.

SKU

355299E0T500

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com