

ScandTag Thermo TC 195M

FACESTOCK

ScandTag Thermo TC 195M is a white woodfree card, coated with thermosensitive coating (black imaging) and - topcoating. It has a good resistance to moisture, oil, fat, alcohol et.c. - ScandTag Thermo TC 195M can be printed using water based and UV inks and varnishes, designed for use - with direct thermal label papers,. - This thermosensitive product is designed for thermal print speeds up to 200 mm/s, depending on printer set up. - Reverse side is coated and has a smooth, semi-matt finish, suitable for printing with all conventional roll - conversion technologies. - It is recommended that customers assess both the pre-print and the overprint characteristics under end use - conditions before proceeding to long runs.

Type

Paper

Top Coating

Yes

Image color

Black

Printing speed (Max.)

200mm/s

PROPERTIES

METHOD

VALUE

Basis Weight

ISO 536

195 ± 15g/m²

Caliper

ISO 534

189 ± 15μ

Gloss

ISO 8254-1 (Tappi 75°) RS

35%

Brightness

ISO 2470 (R457-)

> 78%

Smoothness

ISO 5627 (Bekk)

> 500s

Roughness

ISO 8791 (PPS) RS

2¼

FINAL PRODUCT

Format

Roll

Material Shelf Life

Min. 2 years, stored at 20°C/50% RH - N.B.: When labels are exposed to very high humidity conditions and are in direct contact with the packaging, it is - essential that appropriate water resistant varnish is used to prevent surface picking.

SKU

300099E0T520

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

