

## ScandTag Transfer 150

### FACESTOCK

ScandTag Transfer 150 is a white, coated paper with a silk-smooth semi-matt surface. - The paper has high bulk, opacity and stiffness and is suitable for printing and conversion by all conventional - printing technologies. - It is compatible with a wide range of wax and wax/resin thermal transfer ribbons. It is recommended that customers assess both the pre-print and the overprint characteristics under end use - conditions before proceeding to long runs.

**Type**  
Paper

PROPERTIES	METHOD	VALUE
<b>Basis Weight</b>	ISO 536	150 ± 15g/m <sup>2</sup>
<b>Caliper</b>	ISO 534	132 ± 15µ
<b>Opacity</b>	ISO 2471	97,5%
<b>Gloss</b>	ISO 8254-1	30%
<b>Whiteness</b>	ISO 11475, D 65 10°	119%

### FINAL PRODUCT

**Format**  
Roll

**Material Shelf Life**

Min. 2 years, stored at 20°C/50% RH - N.B.: When labels are exposed to very high humidity conditions and are in direct contact with the packaging, it is - essential that appropriate water resistant varnish is used to prevent surface picking.

**SKU**  
535099X0T900

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

**ADDRESS:**

Beontag  
Pål Anders väg 4, 263 35  
Höganäs, Sweden  
+46 42 25 00 50

[orders.scandstick@beontag.com](mailto:orders.scandstick@beontag.com)