

ScandTag Transfer 150

FACESTOCK

ScandTag Transfer 150 is a white, coated paper with a silk-smooth semi-matt surface. - The paper has high bulk, opacity and stiffness and is suitable for printing and conversion by all conventional - printing technologies. - It is compatible with a wide range of wax and wax/resin thermal transfer ribbons. It is recommended that customers assess both the pre-print and the overprint characteristics under end use - conditions before proceeding to long runs.

Type
Paper

PROPERTIES	METHOD	VALUE
Basis Weight	ISO 536	150 ± 15g/m ²
Caliper	ISO 534	132 ± 15µ
Opacity	ISO 2471	97,5%
Gloss	ISO 8254-1	30%
Whiteness	ISO 11475, D 65 10°	119%

FINAL PRODUCT

Format
Roll

Material Shelf Life

Min. 2 years, stored at 20°C/50% RH - N.B.: When labels are exposed to very high humidity conditions and are in direct contact with the packaging, it is - essential that appropriate water resistant varnish is used to prevent surface picking.

SKU
535099X0T900

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com