

FSC ScandCoat Gloss SSP 713 HG0



FACESTOCK

Scandcoat Gloss is a woodfree, multicoated glossy art paper and board for extremely demanding image – printing. – Scandcoat Gloss is suitable for most known print processes, such as offset, flexo, screen and digital. Besides – conventional inks, the paper produces excellent results with UV and hybrid UV inks. – The paper is UV varnishable and can be overlaminated, foil blocked and embossed.

Type
Paper

PROPERTIES	METHOD	VALUE
Basis Weight	ISO 536	115g/m ²
Caliper	ISO 534	86µ
Opacity	ISO 2471	96%
Gloss	ISO 8254-1 TAPPI 75	68%
Whiteness	ISO 11475, CIE D65/10	130%

REGULATORY APPROVAL
FSC
Yes

BACKING

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Type
Paper

DESCRIPTION	METHOD	VALUE
Caliper	ISO 534	49 ± 3µ
Transparency	ISO 2469	50%

FINAL PRODUCT

DESCRIPTION	VALUE
Typical Caliper	144 ± 10µ

Format
Roll

Certificate

The product is registered to SAI-COC-010567 FSC™ Mix credit.

Regulations

Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs. Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.

Material Shelf Life

24 months stored at 20°C/50% RH

SKU

F505000H0N000

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com