

# FSC ScandPrint V SSP 713 HG0



## FACESTOCK

ScandPrint V is a versatile white calendered woodfree paper, specially selected for use in both simple primary label applications and thermal transfer overprinting. The surface is suitable for solids, sharp halftones and clear text including small type faces by traditional print methods. ScandPrint V may also be used as suitable media for most thermal transfer bar code label printers and print and apply label applicators, with suitable wax or wax/resin ribbons. ScandPrint V has both high smoothness to give an even transfer of ink from the ribbon to the paper and suitable absorbency to allow excellent ink key and smudge resistance.

**Type**  
Paper

PROPERTIES	METHOD	VALUE
<b>Basis Weight</b>	ISO 536	73 ± 3g/m <sup>2</sup>
<b>Caliper</b>	ISO 534	72 ± 4μ
<b>Opacity</b>	ISO 2471	87%
<b>Whiteness</b>	ISO 11475	147%

## REGULATORY APPROVAL

**FSC**  
Yes

## BACKING

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

**Type**  
Paper

DESCRIPTION	METHOD	VALUE
<b>Caliper</b>	ISO 534	49 ± 3μ
<b>Transparency</b>	ISO 2469	50%

## FINAL PRODUCT

DESCRIPTION	VALUE
<b>Typical Caliper</b>	130 ± 10μ

**Format**  
Roll

**Certificate**

The product is registered to SAI-COC-010567 FSC™ Mix credit.

**Regulations**

Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs. Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.

**Material Shelf Life**

12 months stored at 20°C/50% RH

**SKU**

F100000H0N000

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

**ADDRESS:**

Beontag  
Pål Anders väg 4, 263 35  
Höganäs, Sweden  
+46 42 25 00 50

[orders.scandstick@beontag.com](mailto:orders.scandstick@beontag.com)