

FSC Scandtherm TCS AFE SSP 713 40g HG0



FACESTOCK

ScandTherm TCS is a protected direct chemi-thermal label, which is a woodfree paper with a coating of thermosensitive dyes which turn black when heated. There is a top coating which protects the label surface and thermally printed images from above, against contaminants such as moisture, oil, grease and plasticisers from films. ScandTherm TCS can be printed by water based and UV inks and varnishes designed for use with direct thermal papers. This thermal paper has a standard sensitivity making it suitable for print speeds up to 200-250mm per second depending on printer settings. It is recommended that customers assess both the pre-print and the overprint characteristics under end use conditions before proceeding to long runs..

Type

Paper

Top Coating

Yes

Image color

Black

Printing speed (Max.)

200 mm/s

PROPERTIES

METHOD

VALUE

Basis Weight

ISO 536

75 ± 5g/m²

Caliper

ISO 534

80 ± 8µ

REGULATORY APPROVAL

FSC

Yes

ADHESIVE

SSP713 has excellent initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Particularly good adhesion to cardboard, plastic and glass. Note: Not advised for labelling highly plasticised materials, eg: flexible PVC

General purpose permanent

Type

Permanent

Min. Application Temperature

8°C

Min. Service Temperature

-10°C

Max. Service Temperature

70°C

REGULATORY APPROVAL

Direct Food

Yes

Indirect Food

Yes

Food contact

Complies with FDA175.105, BfR XIV.

ISEGA approved for direct contact with dry and moist non-fatty foods

Yes

BACKING

High money glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Type Paper		
DESCRIPTION	METHOD	VALUE
Caliper	ISO 534	49 ± 3μ
Transparency	ISO 2469	50%

FINAL PRODUCT	
DESCRIPTION	VALUE
Typical Caliper	149 ± 15μ
Format Roll	
Certificate The product is registered to SAI-COC-010567 FSC™ Mix credit.	
Regulations Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs. Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.	
Material Shelf Life 12 months stored at 20°C/50% RH	
SKU F300000H1N800	
Replaces all previous information.	

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com