

Scandart Gloss 130 SSP E60 HG0

DESCRIPTION

The values indicated in this leaflet are not intended to be a specification but a guide to the values that may generally be expected. Customers should independently determine, prior to use, the suitability of any material for a specific purpose. All information is subject to change without notice.

FACESTOCK

Scandart Gloss 130 is a woodfree, multicoated glossy art paper and board for extremely demanding image printing. Scandart Gloss 130 is suitable for most known print processes, such as offset, flexo, screen and digital. Besides conventional inks, the paper produces excellent results with UV and hybrid UV inks. The paper is UV varnishable and can be overlaminated, foil blocked and embossed.

Type
Paper

PROPERTIES	METHOD	VALUE
Basis Weight	ISO 536	130g/m ²
Caliper	ISO 534	96μ
Opacity	ISO 2471	95,5%
Gloss	TAPPI 75 ISO 8254-1	72%
Whiteness	ISO 11475	125%

ADHESIVE

ScandStick SSP E60 is a highly versatile permanent adhesive which will adhere to a wide variety of surfaces, both at room temperature and under chill conditions. SSP E60 has been designed to resist edge lift on narrow radius tubes and curved surfaces. SSP E60 has excellent conversion characteristics ensuring consistent waste stripping and label dispensing. It is also suitable for on-press delamination to allow printing on the adhesive surface or tack neutralisation. Although SSP E60 will tolerate some surface condensation, excessive amount of moisture present will reduce the adhesion.

General purpose permanent

Type Permanent	Min. Application Temperature 5°C	Min. Service Temperature -20°C
Max. Service Temperature 100°C		

PROPERTIES	METHOD	VALUE
Peel	FTM 1 (20 min)	13N
Tack	FTM 9	14N

REGULATORY APPROVAL

Direct Food Yes	Indirect Food Yes	Food contact
---------------------------	-----------------------------	---------------------

Meets composition requirement of indirect food additives regulation FDA175.105, BfR XIV.

ISEGA approved for direct contact with dry and moist non-fatty foods
Yes

BACKING

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Type
Paper

DESCRIPTION	METHOD	VALUE
Caliper	ISO 534	49 ± 3µ
Transparency	ISO 2469	50%

FINAL PRODUCT

DESCRIPTION	VALUE
Typical Caliper	154 ± 10µ

Format
Roll

Material Shelf Life
24 months stored at 20°C/50% RH

SKU
B505100I0N000

Last update: 01/05/2024

ADDRESS:
Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50
orders.scandstick@beontag.com