

ScandFilm K200

FACESTOCK

ScandFilm K200 is a super white opaque polypropylene film with a corona treated print surface. – ScandFilm K200 has a fine balance of flexibility and rigidity to suit most general label dispensing and application – requirements. – ScandFilm K200 is also a durable material with a very high tear strength and resistance to moisture and many – chemicals. – ScandFilm K200 is designed for use in pressure sensitive labelling where superior appearance and graphics – are desired. Excellent UV printability. – Conversion is recommended to take place within 6 months of delivery, and always in combination with in-line – corona treatment for optimum performance.

Label film is approved for direct food contact according to
FDA 21 CFR 177-1520

Type
Film

PROPERTIES	METHOD	VALUE
Basis Weight	ISO 536	244 ± 3g/m ²
Caliper	ISO 534	200 ± 5µ

FINAL PRODUCT

DESCRIPTION	VALUE
Typical Caliper	200 ± 5µ

Format
Roll

SKU
952199X0T903

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com