

ScandFilm K80 SSP 713 28g HG0

FACESTOCK

ScandFilm K80 is a super white opaque polypropylene film with a corona treated print surface. - ScandFilm K80 has a fine balance of flexibility and rigidity to suit most general label dispensing and application - requirements. - ScandFilm K80 is also a durable material with a very high tear strength and resistance to moisture and many - chemicals. - ScandFilm K80 is designed for use in pressure sensitive labelling where superior appearance and graphics are - desired. Excellent UV printability. - Conversion is recommended to take place within 6 months of delivery, and always in combination with in-line - corona treatment for optimum performance.

Type

Film

PROPERTIES

METHOD

VALUE

Basis Weight

ISO 536

107 ± 3g/m²

Caliper

ISO 534

80 ± 3μ

ADHESIVE

SSP713 has excellent initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Particularly good adhesion to cardboard, plastic and glass. Note: Not advised for labelling highly plasticised materials, eg: flexible PVC

General purpose permanent

Type

Permanent

Min. Application Temperature

8°C

Min. Service Temperature

-10°C

Max. Service Temperature

70°C

REGULATORY APPROVAL

Direct Food

Yes

Indirect Food

Yes

Food contact

Complies with FDA175.105, BfR XIV.

ISEGA approved for direct contact with dry and moist non-fatty foods

Yes

BACKING

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Type

Paper

DESCRIPTION

METHOD

VALUE

Caliper

ISO 534

49 ± 3μ

Transparency

ISO 2469

50%

FINAL PRODUCT

DESCRIPTION	VALUE
Typical Caliper	143 ± 10μ
Format Roll	
Regulations Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs. Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.	
Material Shelf Life 6 months stored at 20°C/50% RH	
SKU 952000H0N800	
Replaces all previous information.	

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com