

ScandFilm PP75 MW SSP 713 HG0

FACESTOCK

ScandFilm PP75 MW is a matt, white, topcoated, orientated polypropylene film. The matt surface has - characteristics which makes it very suitable for thermal transfer printing. - ScandFilm PP75 MW has good resistance to moisture, oils and many chemicals. When applied to - polypropylene items, ScandFilm PP75 MW can be recycled. The film is free from vinyl chloride and will not - create undesirable atmospheric emissions when burnt. - ScandFilm PP75 MW can be printed by flexography, screen, letterpress, offset lithography.

Type

Film

PROPERTIES

METHOD

VALUE

Basis Weight

ISO 536

66 ± 3g/m²

Caliper

ISO 534

75 ± 5μ

Gloss

ASTM D2457 (45°)

63%

BACKING

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

Type

Paper

DESCRIPTION

METHOD

VALUE

Caliper

ISO 534

49 ± 3μ

Transparency

ISO 2469

50%

FINAL PRODUCT

DESCRIPTION

VALUE

Typical Caliper

133 ± 13μ

Format

Roll

Regulations

Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs. Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.

Material Shelf Life

12 months stored at 20°C/50% RH

SKU

713600H0N000

Replaces all previous information.

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:

Beontag
Pål Anders väg 4, 263 35
Höganäs, Sweden
+46 42 25 00 50

orders.scandstick@beontag.com