

# ScandPrint V SSF 933 HG0

## FACESTOCK

ScandPrint V is a versatile white calendered woodfree paper, specially selected for use in both simple primary - label applications and thermal transfer overprinting. - The surface is suitable for solids, sharp halftones and clear text including small type faces by traditional print - methods. - ScandPrint V may also be used as suitable media for most thermal transfer bar code label printers and print and - apply label applicators, with suitable wax or wax/resin ribbons. - ScandPrint V has both high smoothness to give an even transfer of ink from the ribbon to the paper and suitable - absorbency to allow excellent ink key and smudge resistance.

### Type

Paper

PROPERTIES	METHOD	VALUE
<b>Basis Weight</b>	ISO 536	73 ± 3g/m <sup>2</sup>
<b>Caliper</b>	ISO 534	72 ± 4µ
<b>Opacity</b>	ISO 2471	87%
<b>Whiteness</b>	ISO 11475	147%

## ADHESIVE

SSF933 has excellent initial tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. SSF933 is specially designed for use at low temperature and freezer conditions. For applications on cardboard in temperatures warmer than 0 °C we recommend the SSP 50N or the SSP 713.

Deep freeze permanent

<b>Type</b> Permanent	<b>Min. Application Temperature</b> -20°C	<b>Min. Service Temperature</b> -40°C
<b>Max. Service Temperature</b> 50°C		

PROPERTIES	METHOD	VALUE
<b>Peel</b>	FTM 1 (20 min)	5,5N
<b>Tack</b>	FTM 9	12N

## REGULATORY APPROVAL

### Food contact

Meets composition requirement of indirect food additives regulation FDA 21-CRF 175.105

ISEGA approved for direct contact with dry and moist non-fatty foods  
No

## BACKING

HG0 honey glassine backing allows high speed conversion and consistent dispensing on a wide range of equipment.

### Type

Paper

DESCRIPTION	METHOD	VALUE
Caliper	ISO 534	49 ± 3μ
Transparency	ISO 2469	50%

FINAL PRODUCT	
DESCRIPTION	VALUE
Typical Caliper	131 ± 10μ
<b>Format</b> Roll	
<b>Regulations</b> Food Packaging Applications: The adhesive raw materials are listed under European/US food packaging regulations (BgVV XIV or FDA 21 175.105) and are safe for use in limited contact with foodstuffs. Toy and Packaging Regulations: The materials used have been tested and comply with the current heavy metals regulations EN71-3 Safety of Toys and the UK Packaging (Essential Requirements) Regulations 1998.	
<b>Material Shelf Life</b> 6 months stored at 20°C/50% RH	
<b>SKU</b> 100000K0N000	
Replaces all previous information.	

Last update: 01/05/2024

1. All information, recommendations and descriptions of our Products are based on research, tests and data believed to be reliable and as such they must be considered as a guide and not as a guarantee nor a warranty. 2. Tests must be conducted by the customer to determine suitability of the products for their purposes and/or ambient, in any application and condition. 3. This document is valid only as information and can be revised without notice. For values and other technical product specifications, contact our Sales or Technical Department.

ADDRESS:  
Beontag  
Pål Anders väg 4, 263 35  
Höganäs, Sweden  
+46 42 25 00 50  
[orders.scandstick@beontag.com](mailto:orders.scandstick@beontag.com)