

# Not a Current Stock Product

Please contact our team for assistance.

- Autoadhesivo
- Acrylic
- Film

## 3.2 Mil White Flex Vinyl / TR440 @ .80 Cwt. / 92# Sta Flat L-3

FRONTAL		
A 3.2 Mil white vinyl with polymeric plasticizers, formulated to provide optimum performance with pressure sensitive adhesives.		
Tipo Film		
Tensile MD 3900	Tensile CD 3800	
Tear MD 100	Tear CD 100	
PROPIEDADES		VALOR
Espesor		3.2
APROBACIÓN REGLAMENTARIA		
RoHS Si	Prop65 Si	REACH Si
TPCH Si	CPSIA Si	UL No
FSC No		

ADHESIVO		
A specialty clear acrylic adhesive showing good initial removable tack with high shear and high removable adhesion. This adhesive has excellent clarity & minimum cold flow. Good removability on a wide range of substrates including corrugated and many plastic surfaces.		
Tipo Removable	Composición Acrylic	Shear 0
PROPIEDADES		VALOR
Stainless Steel		4.6 lbs/linear in.
Adhesividad Vidrio		3lbs/linear in.
Polyethylene		1.4
Corrugated		1.20 lbs./in.
Painted Metal		4.1 lbs/linear in.

<b>Loop Tack</b>		1.70 oz/in <sup>2</sup>
<b>APROBACIÓN REGLAMENTARIA</b>		
<b>RoHS</b> Si	<b>Prop65</b> No	<b>REACH</b> Si
<b>TPCH</b> Si	<b>CPSIA</b> Si	<b>Contacto directo con los alimentos</b> No
<b>Contacto indirecto con los alimentos</b> Si		

<b>LINER</b>		
A bleached poly coated kraft which has been silicone coated one side to give a controlled release. This paper has high internal strength to withstand all conventional processing.		
<b>Tensile MD</b> 58	<b>Tensile CD</b> 25	
<b>Tear MD</b> 110	<b>Tear CD</b> 100	
<b>DESCRIPCIÓN</b>	<b>VALOR</b>	
<b>Gramaje</b>	0	
<b>Espessor</b>	6,9	
<b>APROBACIÓN REGLAMENTARIA</b>		
<b>RoHS</b> Si	<b>Prop65</b> Si	<b>REACH</b> Si
<b>TPCH</b> Si	<b>CPSIA</b> Si	

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

DIRECCIÓN:  
Beontag  
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana  
Campo Mourão - PR, Brasil  
+55 (44) 3518-3500