

# Not a Current Stock Product

Please contact our team for assistance.

Autoadhesivo Hotmelt Ru

# Cast Coated / SSP 50N

## **FRONTAL**

A premium cast coated C1S white high gloss paper with a smooth print surface that offers excellent receptivity and print characteristics. The 90% gloss rating provides for the desired wet look label graphics that product manufacturers desire to enhance sales activity.

Tipo Paper

**Tensile MD Tensile CD** 25 Lbs/in 0 Lbs/in **Tear MD Tear CD** 35 Grams 40 Grams

**PROPIEDADES VALOR** 

57 # Rm 24 x 26 Gramaje

3.70 Mil **Espessor** 

**APROBACIÓN REGLAMENTARIA** 

Prop65 **RoHS REACH** Si Si Si **TPCH CPSIA** UL Si Si No

**FSC** No

## **ADHESIVO**

General purpose, strong permanent adhesive with good chill characteristics. ScandStick Permanent 50N has excellent initial tack with high bond strength at elevated, room and chilled temperatures, as well as in moist conditions. It has been formulated to adhere to a wide variety of substrates, including corrugated cardboard, low surface energy materials like polyethylene and non-polar surfaces. SSP 50N provides enhanced conversion characteristics, allowing die-cutting at higher speeds and is designed for both paper and synthetic face materials. Limitation: Not suitable for labelling plasticized

<b>Tipo</b> Perm	<b>Composición</b> Hotmelt Ru
PROPIEDADES	VALOR
Adhesividad Vidrio Polyethylene	0lbs/linear in.

## **APROBACIÓN REGLAMENTARIA**

RoHS Prop65 REACH
Si Si Si

TPCHCPSIAULSiSiNo

Contacto directo con los alimentos Contacto indirecto con los alimentos FDA 21 CFR 175.105

No Si No

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

#### DIRECCIÓN:

Beontag Avenida Presidente Kennedy, 2427 - Jardim Lar Parana Campo Mourão - PR, Brasil +55 (44) 3518-3500