

Not a Current Stock Product

Please contact our team for assistance.

- Autoadhesivo
- Hotmelt Ru
- Paper

FSC ScandCoat MC / SSP 50N / 40#BG



The mark of responsible forestry

FRONTAL

ScandCoat MC is a medium gloss machine coated paper with good whiteness. It is a versatile paper which is suitable for a very wide range of primary label work. Developed for general color printing, ScandCoat MC gives good color lift and can be printed by flexography, rotary or flat-bed letterpress, offset lithography, screen process and can be foil blocked and varnished. It can also be thermal transfer overprinted with suitable smudge resistant ribbons.

Tipo  
Paper

| PROPIEDADES | VALOR     |
|-------------|-----------|
| Gramaje     | 53 lbs/rm |
| Espesor     | 2.7 Mil   |

APROBACIÓN REGLAMENTARIA

|            |              |             |
|------------|--------------|-------------|
| RoHS<br>Si | Prop65<br>Si | REACH<br>Si |
| TPCH<br>Si | CPSIA<br>Si  | UL<br>No    |
| FSC<br>Si  |              |             |

ADHESIVO

General purpose, strong permanent adhesive with good chill characteristics. ScandStick Permanent 50N has excellent initial tack with high bond strength at elevated, room and chilled temperatures, as well as in moist conditions. It has been formulated to adhere to a wide variety of substrates, including corrugated cardboard, low surface energy materials like polyethylene and non-polar surfaces. SSP 50N provides enhanced conversion characteristics, allowing die-cutting at higher speeds and is designed for both paper and synthetic face materials. Limitation: Not suitable for labelling plasticized

|              |                           |
|--------------|---------------------------|
| Tipo<br>Perm | Composición<br>Hotmelt Ru |
|--------------|---------------------------|

| PROPIEDADES        | VALOR           |
|--------------------|-----------------|
| Adhesividad Vidrio | 0lbs/linear in. |

|  |  |                          |
|--|--|--------------------------|
| Polyethylene0                            |  |                          |
| APROBACIÓN REGLAMENTARIA                 |  |                          |
| RoHS<br>Si                               | Prop65<br>Si                               | REACH<br>Si              |
| TPCH<br>Si                               | CPSIA<br>Si                                | UL<br>No                 |
| Contacto directo con los alimentos<br>No | Contacto indirecto con los alimentos<br>Si | FDA 21 CFR 175.105<br>No |

|  |                         |                    |
|--|-------------------------|--------------------|
| <b>LINER</b>   |                         |                    |
| White glassine liner silicone coated on one side. Supports all conventional processing operations. |                         |                    |
| <b>Tipo</b><br>colacril liner  |                         |                    |
| <b>Tensile MD</b><br>34  | <b>Tensile CD</b><br>15 |                    |
| <b>Tear MD</b><br>32   | <b>Tear CD</b><br>26    |                    |
|  |                         |                    |
| <b>DESCRIPCIÓN</b>   | <b>VALOR</b>            |                    |
| <b>Gramaje</b>   | 37                      |                    |
| <b>Espessor</b>  | 2                       |                    |
|  |                         |                    |
| <b>APROBACIÓN REGLAMENTARIA</b>  |                         |                    |
| <b>RoHS</b><br>Si  | <b>Prop65</b><br>Si     | <b>REACH</b><br>Si |
| <b>TPCH</b><br>Si  | <b>CPSIA</b><br>Si      | <b>UL</b><br>No    |
| <b>Contacto directo con los alimentos</b><br>No  |                         |                    |

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

DIRECCIÓN:  
Beontag  
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana  
Campo Mourão - PR, Brasil  
+55 (44) 3518-3500