

Not a Current Stock Product

Please contact our team for assistance.

Autoadhesivo Acrylic Paper

Techni-Therm III / Permanent

FRONTAL

A coated one side thermal transfer facestock with outstanding ink receptivity and print characteristics. It also offers good flexibility and high internal strength for ease in converting. This facestock also offers a 90% brightness and an 82% opacity.

Tipo Paper

Tensile MD Tensile CD 25 Lbs/in 16 Lbs/in Tear MD Tear CD 34 Grams 36 Grams

PROPIEDADES VALOR

44lbs/3300 sq ft Gramaje

2.65 Mil **Espessor Opacidad** 8.2 **Brightness** 90

APROBACIÓN REGLAMENTARIA

RoHS Prop65 **REACH** Si Si Si **TPCH CPSIA** UL Si Si No

FSC No

ADHESIVO

A general purpose acrylic adhesive showing good initial tack with high shear and ultimate adhesion. It has good plasticizer, UV and solvent resistance. This adhesive displays excellent die-cutting and stripping characteristics and has good adhesion to many different substrates.

Tipo Permanent	Composición Acrylic
PROPIEDADES	VALOR
Adhesividad Vidrio	2.8 lbs/linear in.
Polyethylene	1.5

APROBACIÓN REGLAMENTARIA

 RoHS
 Prop65
 REACH

 Si
 Si
 Si

TPCH CPSIA Contacto directo con los alimentos

Si Si S

Contacto indirecto con los alimentos

Si

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

DIRECCIÓN:

Beontag Avenida Presidente Kennedy, 2427 - Jardim Lar Parana Campo Mourão - PR, Brasil +55 (44) 3518-3500