

# Not a Current Stock Product

Please contact our team for assistance.

Autoadhesivo    Acrylic

TM-55 / LPG @ 0.6 Cwt.

<b>ADHESIVO</b> A specialty microsphere repositionable acrylic adhesive designed for roll to roll applications. This adhesive removes cleanly from most papers and a wide variety of substrates. Due to it\'s unique nature, TM55 cannot be coupled with any face/liner combination to achieve guaranteed lay flat properties.		
<b>Tipo</b> Removable	<b>Composición</b> Acrylic	
<b>PROPIEDADES</b>	<b>VALOR</b>	
<b>Adhesividad Vidrio</b>	0.3 lbs/linear in.	
<b>Polyethylene</b>	0	
<b>APROBACIÓN REGLAMENTARIA</b>		
<b>RoHS</b> Si	<b>Prop65</b> Si	<b>REACH</b> Si
<b>TPCH</b> Si	<b>CPSIA</b> Si	<b>Contacto directo con los alimentos</b> No
<b>Contacto indirecto con los alimentos</b> Si		

WARRANTY: All data obtained through ASTM standards and are typical and should not be used for specification purposes. Because of the variety of possible uses, the buyer should test the suitability of each intended use. The buyer assumes all risks in connection with such use. BEONTAG will not be liable for damages in excess of the purchase price of Products or for incidental or consequential damages.

BEONTAG warrants the products to be free from defects in material and workmanship. Should any failure to conform to this warranty appear within one year after the initial date of shipment (unless otherwise stated), BEONTAG shall, upon notification thereof and substantiation that the products have been stored and applied in accordance with BEONTAG'S standards, correct such defects by suitable repair or replacement without charge at BEONTAG's plant or at the location of the products (at BEONTAG's election); provided, however, if BEONTAG determines that repair or replacement is not commercially practical, BEONTAG shall issue a credit in favor of BUYER in an amount not to exceed the purchase price of the products

DIRECCIÓN:  
Beontag  
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana  
Campo Mourão - PR, Brasil  
+55 (44) 3518-3500