

Produto não existe

Não existe

- Autoadesivo
- Latex
- Film

ScandFilm PP60 W TC / AP151 Opaque @ 1.30 Cwt. / 1.5 MIL CLEAR PET LINER L-3C

FRONTAL

ScandFilm PP60 W TC is a super white opaque polypropylene film with a proprietary cavitated core giving high yield and excellent opacity. It is topcoated with a new versatile printable coating. ScandFilm PP60 W TC has a fine balance of flexibility and rigidity to suit most general label dispensing and application requirements. ScandFilm PP60 W TC G is also a durable material with a very high resistance to moisture and many chemicals. ScandFilm PP60 W TC is designed for use in pressure sensitive labelling where superior appearance and graphics are desired. Excellent UV printability. ScandFilm PP60 W TC is not recommended for fan folding.

Tipo

Film

Top Coating

Sim

PROPRIEDADES	MÉTODO	VALOR
Gramatura (g/m²)	ISO 536	45,4 ± 3g/m²
Espessura (µ)	ISO 534	60 ± 3µ
Gloss	ASTM-D2457 (45°)	63

ADESIVO

An outstanding general purpose permanent opaque adhesive that has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting and stripping traits. Provides opacity for cover up applications.

Tipo

Permanent

Composição

Latex

Shear

80

PROPRIEDADES	VALOR
Stainless Steel	7.3 lbs/linear in.
Glass	5,7 lbs/linear in.
Polyethylene	6,5
Corrugated	2.50 lbs./in.
Painted Metal	7.0 lbs/linear in.
Loop Tack	5.00 oz/in²

REGULATÓRIOS

RoHS Sim	Prop65 Não	REACH Sim
TPCH Sim	CPSIA Sim	Contato direto com alimentos Não
Contato indireto com alimentos Sim		

LINER A 1.5 Mil clear pet liner which is silicone coated one side to give a controlled release. Uniform caliper and high internal strength enhance the excellent die-cutting characteristics of this liner.		
Tipo 17617		
Tensile MD 32000	Tensile CD 0	
Tear MD 0	Tear CD 0	
PROPRIEDADES	VALOR	
Espessura (μ)	1.5	
REGULATÓRIOS		
RoHS Sim	Prop65 Sim	REACH Sim
TPCH Sim	CPSIA Sim	UL Não
Contato direto com alimentos Não		

teste

ENDEREÇO:
Beontag
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana
Campo Mourão - PR, Brasil
+55 (44) 3518-3500