

Produto não existe

Não existe

- Autoadesivo
- Latex
- Paper

Techni-Therm Direct NTC / AP151 / 40#SCK L-3

FRONTAL		
A medium sensitivity, non-topcoated direct thermal label facestock designed for short-duration applications in dry environments. This paper has an initial activation temperature of 185°F and an effective activation temperature of 280°F. This product contains BPS which is known to the state of California to cause cancer, birth defects, or other reproductive harm (Prop 65).		
Tipo Paper		
Tensile MD >21	Tensile CD 11.5 lbs.in	
PROPRIEDADES	VALOR	
Gramatura (g/m²)	47 lbs/rm	
Espessura (µ)	3.03 mil	
REGULATÓRIOS		
RoHS Sim	Prop65 Não	REACH Sim
TPCH Sim	CPSIA Sim	UL Não
FSC Não		

ADESIVO		
An improved general purpose permanent rubber based adhesive which has high initial tack and high ultimate adhesion. It is recommended for high speed wide web processing and can be used on many different substrates. Displays excellent die-cutting & stripping traits.		
Tipo Permanent	Composição Latex	Shear 80
PROPRIEDADES	VALOR	
Stainless Steel	7.3 lbs/linear in.	
Glass	5.7 lbs/linear in.	
Polyethylene	6.5	
Corrugated	2.50 lbs./in.	
Painted Metal	7.0 lbs/linear in.	
Loop Tack		

5.00 oz/in ²		
REGULATÓRIOS		
RoHS Sim	Prop65 Não	REACH Sim
TPCH Sim	CPSIA Sim	Contato direto com alimentos Sim
Contato indireto com alimentos Sim		

LINER		
A super calendared kraft paper which has been silicone coated one side to give a controlled release. This paper has a hard, smooth caliper for a consistent surface. Due to it's high internal strength, it will withstand all conventional processing operations including: die-cutting, butt cutting, line scoring, and dispersing.		
Tipo 5517342		
Tensile MD 30 Lbs/In	Tensile CD 20 Lbs/In	
Tear MD 32 Grams	Tear CD 34 Grams	
PROPRIEDADES		
Gramatura (g/m²)	40.5 Lbs/Rm	
Espessura (μ)	2.5 Mil	
REGULATÓRIOS		
RoHS Sim	Prop65 Sim	REACH Sim
TPCH Sim	CPSIA Sim	UL Não
Contato direto com alimentos Não		

teste

ENDEREÇO:
Beontag
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana
Campo Mourão - PR, Brasil
+55 (44) 3518-3500