

Produto não existe

Não existe

- Autoadesivo
- Acrylic
- Paper

Techni-Therm Direct NTC / AT150

FRONTAL

A medium sensitivity, non-topcoated direct thermal label facestock designed for short-duration applications in dry environments. This paper has an initial activation temperature of 185°F and an effective activation temperature of 280°F. This product contains BPS which is known to the state of California to cause cancer, birth defects, or other reproductive harm (Prop 65).

Tipo

Paper

Tensile MD

>21

Tensile CD

11.5 lbs.in

PROPRIEDADES

VALOR

Gramatura (g/m²)

47 lbs/rm

Espessura (µ)

3.03 mil

REGULATÓRIOS

RoHS

Sim

TPCH

Sim

FSC

Não

Prop65

Não

CPSIA

Sim

REACH

Sim

UL

Não

ADESIVO		
An all temperature and freezer grade acrylic adhesive with good initial tack and high ultimate adhesion when applied at temperatures as low as -20 F. Very good plasticizer, UV and solvent resistance. AT150 adhesive allows for short term reposition on many substrates, yet displays excellent permanency at room temps		
Tipo Permanent	Composição Acrylic	Shear 105
PROPRIEDADES	VALOR	
Stainless Steel	5.4 lbs/linear in.	
Glass	4.4 lbs/linear in.	
Polyethylene	4.2	
Corrugated	1.50 lbs./in.	
Painted Metal	5.2 lbs/linear in.	
Loop Tack		

3.00 oz/in²

REGULATÓRIOS

RoHS

Sim

Prop65

Sim

REACH

Sim

TPCH

Sim

CPSIA

Sim

Contato direto com alimentos

Sim

Contato indireto com alimentos

Sim

teste

ENDEREÇO:

Beontag
Avenida Presidente Kennedy, 2427 - Jardim Lar Parana
Campo Mourão - PR, Brasil
+55 (44) 3518-3500